


DS SERIES

DS653LT5-2


65" 4000 nits High Brightness
Digital Signage Display




SUNLIGHT
VIEWABLE IMAGE




SUSTAINED
HIGH BRIGHTNESS



BUILT-IN
MEDIA PLAYER



THERMAL
MANAGEMENT



TRUECOLOR™
CALIBRATED

Android is a trademark of Google LLC.
The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License.

FOR MORE INFORMATION

For more information about DynaScan, visit our website at www.dynascan.com. Copyright © DynaScan Technology Inc. All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.


DynaScan

SPECIFICATION


MODEL	DS653LT5-2	
PANEL	LCD Panel Size	65"
	Native Resolution	1920 x 1080
	Brightness	4000 nits
	Color Depth	10 bits
	Contrast Ratio	4000 : 1
	Response Time (Typ.)	8 ms (Typ.)
	Viewing Angle	178° / 178°
	Light Lifetime (Typ.)	100,000 hrs
	Polarized Sunglasses Support	Yes
POWER	Power Supply	Internal
	Rated Voltage	100-240V ~ 50/60HZ
	Power Consumption (Typ. /Max.)	255 W / 550 W
	Power Saving Mode	< 1 W
MECHANICAL SPECS	AC Out	< 100 W
	Bezel Width (T/B/L/R)	11.8 / 11.8 / 11.8 / 11.8 mm
	Cabinet Color	Black
	Monitor Dimension (LxHxD)	1456.7 x 829.7 x 89.6 mm
	Monitor Weight	39.1 kg
	Orientation	Portrait / Landscape
	VESA Mounting (LxH)	400 x 400 mm, 600 x 400 mm
	Carrying Handles	Yes
FEATURE	Language	English
	Support SNMP (Up to V3.0)	Yes
	Image Retention Protection	Yes
	Auto Orientation Sensor	Yes
	Ambient Light Sensor	Yes
	Power On/Off Scheduling	Yes
	OSD Menu Rotation	Yes
INPUT	HDMI 2.1 (HDCP 2.3)	x2 (1080p recommended)
	USB 2.0	x2
OUTPUT	Audio	x1
EXTERNAL CONTROL	RS-232	In x1
	RJ-45	x1 (LAN)
	ETK Port (Thermal)	x1
	ESK Port (IR, Ambient)	x1
ENVIRONMENT	Operating Temperature	0° ~ 45° C
	Storage Temperature	-20° ~ 60° C
	Humidity	10% ~ 80% RH Non-condensing
INTERNAL PLAYER	Operating System	Android 11.0
	Processor	Quad-core A53
	Clock Speed	1.5GHz
	Main Memory Interface	DDR4, 2GB
	Graphics	Mali G512
	Storage	Internal: 8GB eMMC Flash
ACCESSORY	Multimedia	4K video decoders, 30/60fps H.264 /VP9 10bit, MPEG-1/2/4
	Quick Start Guide. Power Cord. Remote Control. Batteries. IR & Ambient Sensor	
CERTIFICATION	CE / CB / FCC / ETL / RoHS / PSE	

DIMENSIONS

Unit: mm [inch]



INTERFACE



FOR MORE INFORMATION

For more information about DynaScan, visit our website at www.dynascan.com. Copyright © DynaScan Technology Inc. All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.