


FINE-PITCH LED SERIES

# LN018AQ4

3500 nits Professional High Brightness  
Indoor Direct-View LED



SUPERIOR  
VISIBILITY



EASY PLUG  
CONNECTION



ENERGY  
EFFICIENT



FRONT-  
SERVICEABLE



LIGHTWEIGHT

## FOR MORE INFORMATION


For more information about DynaScan, visit our website at [www.dynascan.com](http://www.dynascan.com). Copyright © DynaScan Technology Inc. All rights reserved.  
All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.

# DynaScan

SPECIFICATION

MODEL	LN018AQ4	
LED Module	LED Type	SMD 1415
	Pitch	1.86mm
	Module Resolution (H x W)	134 x 134 dots
	Pixel Density	287296 dots/m²
	Scan	1/34 Scan
	Refresh Rate	≥3840
	Driver IC	Hi-refresh IC
	Grayscale	12~16bit
	Brightness	3500 Nits
	Color Temp.	2500 - 10000K adjustable
POWER	Viewing Angle	140°(H) / 140°(V)
	Min Viewing Distance	2M
	Light Lifetime (Typ.)	100,000 hrs
MECHANICAL SPECS	Module Dimensions	250mm x 250mm
	Cabinet Dimensions	500 x 500 x 41mm
	Cabinet Area	0.25m²
ENVIRONMENT	Weight	6.3 (kg/Cabnit), 25.2 (kg/m²)
	Operating Temperature	-10° C ~ 50° C
CERTIFICATION	Manufacturing Compliance	CE / FCC / ETL / LVD

DIMENSIONS



FOR MORE INFORMATION

For more information about DynaScan, visit our website at [www.dynascan.com](http://www.dynascan.com). Copyright © DynaScan Technology Inc. All rights reserved. All specifications and descriptions are tentative and subject to change without notice. Reproduction without permission is prohibited.

