


FINE-PITCH LED SERIES

LN025AQ4

3300 nits Professional High Brightness
Indoor Direct-View LED



SUPERIOR
VISIBILITY



EASY PLUG
CONNECTION



ENERGY
EFFICIENT



FRONT-
SERVICEABLE



LIGHTWEIGHT

FOR MORE INFORMATION

For more information about DynaScan, visit our website at www.dynascan.com. Copyright © DynaScan Technology Inc. All rights reserved.
All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.


DynaScan

V1.03

SPECIFICATION

MODEL	LN025AQ4	
	LED Type	SMD 1415
	Pitch	2.5mm
	Module Resolution (H x W)	100 x 100 dots
	Pixel Density	160000 dots/m²
	Scan	1/25 Scan
	Refresh Rate	≥3840Hz
	LED Module	Driver IC
	Grayscale	12~16bit
	Brightness	3300 Nits
	Color Temp.	2500 - 10000K adjustable
	Viewing Angle	140°(H) / 140°(V)
	Min Viewing Distance	5M
	Light Lifetime (Typ.)	100,000 hrs
POWER	Input Voltage	100-240V ~ 2.5A 50/60HZ
	Power Consumption (Typ.)	176 W/m²
	Power Consumption (Max.)	530 W/m²
	Heat Generation (Typ.)	150 BTU/m²
	Heat Generation (Max.)	452 BTU/m²
MECHANICAL SPECS	Module Dimensions	250mm x 250mm
	Cabinet Dimensions	500 x 500 x 41mm
	Cabinet Area	0.25m²
	Weight	6.3 (kg/Cabnit), 25.2 (kg/m²)
ENVIRONMENT	Operating Temperature	-10° C ~ 50° C
CERTIFICATION	Manufacturing Compliance	CE / FCC / ETL / LVD

DIMENSIONS



FOR MORE INFORMATION

For more information about DynaScan, visit our website at www.dynascan.com. Copyright © DynaScan Technology Inc. All rights reserved. All specifications and descriptions are tentative and subject to change without notice. Reproduction without permission is prohibited.

