

EPD SERIES

NVA2AP

28.5" ePaper Display with Protective Glass

NVA2AP



RECYCLED &
RECYCLABLE
MATERIALS




ULTRA
LIGHT & THIN



ANTI-UV
GLASS



DIGITAL
BENEFIT



ULTRA-LOW
POWER

FOR MORE INFORMATION

For more information about DynaScan, visit our website at www.dynascan.com. Copyright © DynaScan Technology Inc. All rights reserved.
All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.


DynaScan

V1.05

SPECIFICATION

MODEL	NVA2AP	
PANEL	Size	28.54 inches
	PPI	131
	Resolution	3060 x 2160
	Pixel Pitch	0.1935 x 0.1935 mm
	Active Display Area (H x V)	589.2 x 415.0 mm
	Contrast Ratio	22:1
	Display Colors	60,000
	Operation Hours	24/7
	Update Time (Typ.)	21s
POWER	Panel Surface	Anti Glare
	Rated Voltage	DC 12V / 2.5A
	Power Consumption (Max)	6W
BATTERY COMPATIBILITY*	Type	18650 lithium battery
	Rated Voltage	3.7V
	Recommended Capacity	>3,000mAh
MECHANICAL SPECS	*Batteries are not included.	
	Dimension	626.20 x 452.0 x 30 mm
	Weight	3.02 kg (TBC)
	Hanging Point	Yes x 4
	Bezel Width (T/B/L/R)	18.5 / 18.5 / 18.5 / 18.5 mm
	Color	Black & Black, White & White
	Protection Glass	1.1mm Ultra clear glass w/optical bonding(UV cut)
USER INTERFACE	VESA Mounting (L x H)	200 x 200 mm
	Orientation	Portrait / Landscape
	Language	English
	Support SNMP (Up to V3.0)	Yes
INPUT	Power On/Off Scheduling	Yes
	USB Type-C	x2(for data x1; for power supply & datax1)
	Mini USB	x1 for WI-charge receiver
INTERNAL PLAYER	Operating System	Android 11
	Clock Speed	2.0GHz
	Graphics	ARM Mail-G52
	Storage	4GB RAM
		32GB eMMC flash
	Bluetooth	5.3 compliant
	Wireless LAN	IEEE802.11a/b/g/n/ac/ax compliant
ENVIRONMENT	Operating Temperature	with Battery 0°~ 45°C, w/o Battery 0°~ 50°C
	Storage Temperature	-25°~ 60°C
	Humidity	20%~80% RH Non-condensing
	Environmental Rating	IK5
CERTIFICATION	CE / FCC / CB / PSE / LVD / ISED / ETL / RoHS 2.0 / RCM / Bluetooth	

DIMENSIONS



INTERFACE

